

S/1500 THERMAL-BARRIER ALUMINUM HORIZONTAL ROLLING WINDOW

WHITE or BRONZE
with 7/8" INSULATING GLASS and EXTRUDED SCREEN
for RESIDENTIAL, APARTMENT, SCHOOL and
INDUSTRIAL BUILDINGS




Coastal
Industries Inc.
MANUFACTURERS OF WINDOWS, DOORS & SCREENS

*THERMAL BARRIER MINIMIZES CONDENSATION,
REDUCES COLD TRANSMISSION and
PROVIDES SUPERIOR INSULATION FROM COLD.*

77 Newark Street
Haverhill, MA 01832

www.ciiwindows.com
Email: sales@ciiwindows.com

Phone: 978-373-1543



SLIDING WINDOW

The Series 1500 Sliding Window

Available in WHITE or BRONZE

With 7/8" insulated glass, clear or colonial

Excellent for COMMERCIAL or RESIDENTIAL apartment buildings



SLIDING PICTURE WINDOW

SPECIFICATIONS

General: Horizontal Rolling Windows shall be Coastal thermally improved Series 1500 manufactured by Coastal Industries, Inc.

Material: All aluminum extrusions shall be 6063-T5 alloy having a minimal wall thickness of .062". Insulation, when required, shall be provided by a poured-in-place polyurethane specially formulated for this purpose. Parting stops shall be black rigid vinyl extrusions. Sections shall be designed to provide complete thermal break in both frames and sash.

Construction: Frame shall be 3 1/4" in depth. Corners shall be coped and mechanically joined with screws. An integral fin frame is standard. A rigid vinyl parting stop at the frame head and a sill insert are provided to prevent thermal short circuit. Sill shall have baffled weep holes for drainage. Sash members shall be designed to accommodate 7/8" sealed insulating glass. Sash corners shall be semi-lap type mechanically joined with stainless steel screws at each corner.

Hardware: Moving sash shall be equipped with two steel ball bearing wheels mounted in nylon wheel housings which allow a vertical adjustment. The moving sash shall have an automatic spring-action latch and can be used in any vertical location.


Weatherstripping: Sash and frame shall be double weatherstripped using Fin-seal or Poly-bond with flexible vinyl as required.

Glazing: Series 1500 shall be glazed with 7/8" sealed insulating glass using "wrap-around" vinyl of the marine type.

Screens: Standard half screens shall have extruded aluminum frames with charcoal fiberglass cloth. Full screens are available on two-panel windows only.

Finish: Standard finish shall be baked acrylic enamel paint in either WHITE or BRONZE.

(Specifications subject to change without notice.)



Installation: (BY OTHERS) All windows shall be installed without racking, binding, forcing or distorting of frames or sash. Sill shall be level and jambs plumb. All caulking shall be sufficient to provide a water tight perimeter seal. It shall not be the responsibility of the manufacturer to insure against faulty or improper installation.