High Value
Superior Quality
Performance/Durability
Stylish Design
Heat/Cold Resistance







Features and Specifications



Novatech Patio Doors'

value-priced series starts with the most advanced vinyl. A highgrade resin unmatched for strength, weight reduction and freedom from wear - they will not rot, rust, pit or blister over long periods of time. The doors ship

knocked down for easy transport



Standard Hardware

Elite handle available in white or black, Optional upgrade to Contemporary handles in white, black, or satin nckel.



Glazing

High-performance glazing with Low-E glass and Super Spacer® technology.

Super Spacer



Optional Locks

Two-Position Kick Locks mount on the bottom of the operating door. Used as secondary lock when the door is closed and available in white, beige, or brown.

Twin-point Locks provide two heavy-duty locking points on the door frame. Available on all hardware handles.

Optional Decorative Grills

Internal grills are available in a wide range of design styles with colours that include Flat **Grills** in two-tone, white, brass and pewter, Georgian **Grills** in two-tone and white, and Pencil Grills in white, brass and pewter.



Frame

- Double perimeter seals
- 47/8" mechanically fastened vinyl frame
- Components easily installed and replaceable
- Stainless steel roller track

Durable Welded Sash


- Reinforced with steel to withstand higher wind loads
- Double perimeter seal for superior air-tightness
- Adjustable nylon tandem ball-bearing rollers
- 1" sealed units for optimal thermal performance

Dimensions Door/Panel Configurations and Finished Sizes


















OXXO-Slide R and Slide L from Centre

2 Panels

59_{1/2} W × 79_{1/2} H 71_{1/2} W × 79_{1/2} H

3 Panels

88_{1/2} W × 79_{1/2} H 106_{1/2} W x 79_{1/2} H

4 Panels

116_{1/2} W × 79_{1/2} H 140_{1/2} W x 79_{1/2} H

Optional Exterior Colours

Novatech patio doors boast a wide range of exterior colour options that feature a durable finish that is also UV stable.



Performance

Standard	Configuration	Performance Class and Grade	Air Leakage	Water Penetration Resistance	Design Pressure
AAMA/WDMA/CSA 101/1.S.2/A440-08 and CSA A440S1-09	0X / X0	R-PG30	A3-0.1 L/s-m ²	220 Pa (4.5 psf)	±1920 Pa (±40 psf)



Most of our products meet the Energy Star program guidelines for helping protect the environment through superior energy efficiency.





Distributed By:

Coastal Industries, Inc. 77 Newark St., Haverhill, MA 01832 978-373-1543 sales@ciiwindows.com www.ciiwindows.com

